

## DEMOLITION PULVERIZER

# MB-PT650








## SPECIFICATIONS

| | | |
|---|---|---|
| Recommended excavator | ton | 6,5 - 13 |
| Recommended backhoe loader | ton | 6 - 10* |
| Main frame weight | ton | 0.49 |
| Speed/Min. (minimum - maximum) | rpm | 20 - 25 |
| Rotation | Degree | 360° |
| Oil pressure (rotation) | bar | 160 - 200 |
| Oil flow rate (rotation) | l/min | 25 - 35 |
| Oil pressure (opening - closing) | bar | 250 - 350 |
| Oil flow rate (opening - closing) | l/min | 70 - 100 |

* Only compatible with the posterior boom of a Backhoe.

## JAW KIT





| | Crusher Kit | Pulverizer Kit | Shear Kit |
|---|---|---|---|
| Kit weight | 0.18 ton | 0.19 ton | 0.19 ton |
| Total weight (with Main frame) | 0.68 ton | 0.69 ton | 0.69 ton |
| Size A | 1045 mm | 860 mm | 850 mm |
| Size B | 710 mm | 710 mm | 710 mm |
| Size C | 1425 mm | 1465 mm | 1440 mm |
| Size D | 220 mm | 300 mm | 185 mm |
| Size E | 565 mm | 550 mm | 300 mm |
| Size H | 535 mm | 535 mm | 420 mm |
| Pick force F1 | 35 ton | 35 ton | 50 ton |
| Blade force F2 | 100 ton | 100 ton | 115 ton |
| Ø Maximum Rebar | 35 mm | 35 mm | - |

## OPTIONAL ACCESSORIES

| | |
|---|---|
| 12 V Electrical Kit (for 2 hose functionality) | 24 Month Warranty |

## APPLICATION AREAS

Demolitions



The data and images provided above are not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice.