



DEMOLITION PULVERIZER

MB-PT1150



SPECIFICATIONS



Recommended excavator	ton	12 - 19
Main frame weight	ton	0.845
Speed/Min. (minimum - maximum)	rpm	20 - 25
Rotation	Degree	360°
Oil pressure (rotation)	bar	180-220
Oil flow rate (rotation)	l/min	30-40
Oil pressure (opening - closing)	bar	250-350
Oil flow rate (opening - closing)	l/min	70-100

JAW KIT



	Crusher Kit	Pulverizer Kit	Shear Kit
Kit weight	0.27 ton	0.35 ton	0.26 ton
Total weight (with Main frame)	1.12 ton	1.2 ton	1.11 ton
Size A	1220 mm	1050 mm	1010 mm
Size B	850 mm	850 mm	850 mm
Size C	1650 mm	1590 mm	1660 mm
Size D	270 mm	380 mm	210 mm
Size E	640 mm	530 mm	315 mm
Size H	635 mm	585 mm	485 mm
Pick force F1	65 ton	65 ton	75 ton
Blade force F2	165 ton	165 ton	180 ton
Ø Maximum Rebar	40 mm	40 mm	-

OPTIONAL ACCESSORIES

12 V Electrical Kit (for 2 hose functionality)

24 Month Warranty

APPLICATION AREAS



Demolitions