DEMOLITION PULVERIZER
MB-PT1650





SPECIFICATIONS

Recommended excavator	ton	19 - 25
Main frame weight	ton	1.235
Speed/Min. (minimum - maximum)	rpm	20 - 25
Rotation	Degree	360°
Oil pressure (rotation)	bar	200 - 250
Oil flow rate (rotation)	l/min	30 - 40
Oil pressure (opening - closing)	bar	300 - 350
Oil flow rate (opening - closing)	l/min	100 - 150

JAW KIT

	Crusher Kit	Pulverizer Kit	Shear Kit
Kit weight	0.43 ton	0.62 ton	0.43 ton
Total weight (with Main frame)	1.63 ton	1.82 ton	1.63 ton
Size A	1340 mm	1160 mm	1160 mm
Size B	850 mm	850 mm	850 mm
Size C	1865 mm	1810 mm	1910 mm
Size D	300 mm	470 mm	245 mm
Size E	710 mm	605 mm	365 mm
Size H	725 mm	680 mm	580 mm
Pick force F1	65 ton	75 ton	90 ton
Blade force F2	190 ton	190 ton	200 ton
Ø Maximum Rebar	40 mm	40 mm	-

OPTIONAL ACCESSORIES

12 V Electrical Kit (for 2 hose functionality)	24 Month Warranty

APPLICATION AREAS

Demolitions

The data and images provided above are not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice.